


GL60

Energy cell 60Ah



Providing our customers with high quality energy storage solutions for both transport & utility applications since 1909.

Datasheet



Technical Data

Nominal Capacity (typical)	60 Ah (measured at C/10 discharge rate, RT)
Nominal Energy	220 Wh (measured at C/10 discharge rate, RT)
Nominal Voltage	3,7 V
Voltage range	3,0 V to 4,2 V
Dimensions	Length (L) 286 mm ± 1 mm
	Width (W) 178,5 mm ± 1 mm (152 mm folded)
	Thickness (T) 12 mm +0,1/-0,5 mm
Weight	1120 g
Volume	475 ml
Housing	Foil packaging
Tabs	Aluminium (+ Pole), Ni-coated Copper (- Pole)
	Length (A) 33 mm ± 1 mm
	Distance (B) 90 mm ± 1 mm
	Width (C) 50 mm ± 0,2 mm
	Thickness 0,3 mm ± 0,02 mm
Cycle Life	8,000 cycles* (1C charge/discharge, at 80% DoD & RT)
	4,500 cycles (1C charge/discharge, at 100% DoD & RT)
Energy density (gravimetric, volumetric)	196 Wh/Kg, 460 Wh/l

Charge

Charging method	CC/CV (Constant Voltage with limited current)
Max. charge voltage	4,2 V (+0,05 V)
Max. charge current	60 A (1C), 20s pulse 180 A (3C)
End of charge	U = 4,2 V and I < C/10
Max. temperature range	0°C to +45°C

Discharge

Max. discharge current	180 A (3C), 20s pulse 300 A (5C)
End of discharge Voltage	3,0 V
Max. temperature range	-20°C to +55°C

Storage and transport

Max. temperature range	-20°C to +25°C for up to 1 year
	+25°C to +40°C for up to 3 months
	+40°C to +60°C for up to 1 week

* Expected

Important Information

This datasheet contains typical information specific to products manufactured at the time of this publication and does not constitute a guarantee or warranty with respect to any cells and batteries. Cells/batteries performance and service life depends on the operating temperature, storage conditions, cut-off voltage and load applied in a specific application. It is the responsibility of each user to ensure that each application is adequately designed in terms of safety and usage conditions, and is in conformance with existing standards and requirements.

Specifications are subject to change without notice.

Leclanché SA (Headquarters)

Avenue des Sports 42
CH - 1400 Yverdon-les-Bains
Switzerland

Leclanché GmbH

Industriestrasse 1
D - 77731 Willstätt
Germany

Leclanché North America, Inc.

12222 Merit Drive
Suite 1550
Dallas, TX 75251, USA

www.leclanche.com

info@leclanche.com



STATIONARY SOLUTIONS



e-TRANSPORT SOLUTIONS



SPECIALTY BATTERY SYSTEMS

WE ARE IN CHARGE